



# Bowers & Wilkins

## **702 S3 Signature**

Technical Information



## Technical Features

Decoupled Carbon Dome tweeter  
Solid Body Tweeter-on-Top  
Continuum™ cone FST™ midrange  
Decoupled midrange  
Aerofoil™ Profile bass cones  
Flowport™

## Description

3-way vented-box system

## Drive Units

1x ø25mm (1 in) Decoupled Carbon Dome high-frequency  
1x ø150mm (6 in) Continuum cone FST midrange  
3x ø165mm (6.5 in) Aerofoil Profile bass

## Frequency Range

-6dB 28Hz - 33kHz

## Frequency Response (+/-3dB from reference axis)

46Hz - 28kHz ±3dB

## Sensitivity (on axis at 2.83Vrms at 1m)

90dB

## Harmonic Distortion

2nd and 3rd harmonics (90dB, 1m on axis)  
<1% 86Hz - 28kHz  
<0.5% 110Hz - 20kHz

## Nominal Impedance

8Ω (minimum 3.1Ω)

## Recommended Amplifier Power

30W - 300W into 8Ω on unclipped programme

## Max. Recommended Cable Impedance

0.1Ω

## Dimensions

Height: 1,010 mm (39.8 in) cabinet only  
1,138 mm (44.8 in) including tweeter and plinth

Width: 192 mm (7.6 in) cabinet only  
290 mm (11.4 in) including plinth

Depth: 354 mm (13.9 in) cabinet only  
410 mm (16.1 in) including plinth  
391 mm (15.4 in) including grille and terminals

## Net Weight

39.5 kg (87.1 lbs)

## Finishes

Cabinet: Datuk Gloss  
Midnight Blue Metallic

Grille: Black